



堆積高度(STACK HEIGHT)=15.6±1mm

NO.	零件名稱 PART NAME	材質 MATERIAL	圖號 ITEM NO.	台量 Q'TY	尺寸 DIM. DESCRIPTION
1	O形圈 O-RING	橡膠 NBR	120-8	1	ID28.5xφ2
2	鋁上塞 TOP COVER	鋁合金 6061/T6	153E-1-3	1	1-1/8"
3	鋁斜管 COMPRESSION RING	鋁合金 6061/T6	153-2	1	1-1/8"
4	密封式軸承 AC SEALED BEARING	軸承鋼 SUJ2	NHB-15	1	OD52x45°x45°
5	上碗 UPPER CUP	鋁合金 6061/T6	285-5	1	φ56 <sup>+0.15</sup> <sub>0</sub>
6.1	阻尼安全下碗 DAMPING SAFETY LOWER CUP	鋁合金 6061/T6	DP01-5	1	φ56 <sup>+0.05</sup> <sub>+0.08</sub>
6.2	密封式軸承 AC SEALED BEARING	軸承鋼 SUJ2	NHB-15C	1	OD52x45°x45°
6.3	下塞 CROWN RACE	鋁合金 6061/T6	DP01-6	1	φ30(φ39.8) <sup>+0</sup> <sub>0</sub>

- 增加轉向阻力提升龍頭穩定度
- 限制龍頭在135°範圍內旋轉之安全車頭碗組
- 1-1/8" 前叉立管
- 鋁合金下塞(內徑30或39.8mm)
- 密封式軸承
- Enhance steering resistance for improved front-end stability
- Restrict the handlebar within a 135° range using a safety headset assembly.
- 1-1/8" Threadless Steerer
- Alloy Crown Race ID 30mm Or 39.8mm
- Sealed Bearing

單位 UNIT	mm	比例 SCALE	1:1	日期 DRAWING DATE	2024.01.10	角法 VIEW	
型號 ITEM NO.	H153E-1DP						版次(REV):A
品名 ITEM NAME	H153E-1DP 阻尼碗組-組立圖(Assembly drawing)						
規格 DIMENSION	1-1/8" x 56/62 x 30(39.8)						
圖號 FIG. NO.	H153E-1DP-組立圖-A						

**neco**®

誌慶工業股份有限公司